
Modular Convenience Counters (MCC) Hot - cleaning (monthly)





Tilt both doors outwards to clean the inside of the innermost door and the back of the shelves. Follow the above steps in reverse order to return both doors to their original positions. Remember to align the slots with the guiding pins first!

Step 18, only Full Serve model


Keep one of the back doors open. Remove the plating of the bottom presentation deck through the opening.

Clean plating and keep aside.



Step 19, only Full Serve model In the same way, remove the plating above the water tray.

Clean plating and keep aside.



Step 1 IMPORTANT: turn off the MCC by pressing the O on the 3 switches. Pull the plug.

Let the unit cool down first!



Step 2 Clean the top glass pane.

Lift and hold the top glass

pane while cleaning it on the

Step 3

insde

Step 5



Step 11 Clean the shelves inside the unit.

Step 9, only Full Serve model

Lift and hold the top glass

while tilting/lowering the

no further. Lower the top

glass back in place.

glass.

front glass until it can move

Step 10, only Full Serve model

Clean the back of the front





Step 4 Lift and hold the top glass pane while removing the transparent air guide pane for cleaning.

Clean the transparent air

Do not use cleaning

polycarbonate.

Step 6

guide pane and place it back.


products that may damage



Step 12, only Full Serve model Lift and hold the top glass while closing the front glass until you hear a snap. Gently lower the top glass back in place.



Slide the double-glass side pane towards the front, along the top guide and bottom guiding rails. Clean both sides while holding it. Don't slide it past the top



Step 7 To clean the guiding rails the side pane can be removed entirely.

The transparent sides of the side pane should face







Backloading models Clean the back doors on the

Solid back models Clean the outside (if the unit's back. You're

To clean the back doors on the inside and the back of the shelves, please follow the next steps.

until its slot aligns with the guiding pin.

Step 15, only backloading models

Now tilt the outermost door outwards along the guiding pin, so you can clean it on the other side.







Step 20, only Full Serve model Remove the air outlet through the back door opening.



Step 21, only Full Serve model Open the front glass pane to remove the air inlet.



Step 22, only Full Serve model Disassemble to clean all loose inlet and outlet parts and reassemble. Keep aside.



Step 23, only Full Serve model Remove and clean the water tray. Also clean the water filler pipe and water level sensor.



Step 13 outside.

accessible) and inside of

ready cleaning!

Step 14, only backloading models

First slide the right (outermost) door open



forward and up when sliding it back in position. Also make sure it fits into the vertical U-profile at the back.





Step 8, only Full Serve model or Self-Serve with doors Clean the front glass (doors) Model with doors: also clean the back of the doors.





Step 16, only backloading models

Then slide both doors to the right until the innermost door's slot aligns with the guiding pin.



Step 24, only Full Serve model Clean the air fans at the front with a brush.

Finally, put all cleaned parts back in reverse order.

Daily Cleaning

- Clean the inside of the unit with hot water and a sustainable cleaner.
- Then wipe with wet cloth to remove detergent.

Weekly Cleaning

- Clean the outside of the unit using a small amount of hot water, a mild cleanser and a soft brush or sponge. After cleaning, dry with a cloth.
- Treat cleaned surfaces with an antibacterial agent. Rub dry with a soft cloth or paper towel.

www.frijado.com

MCC-062021.01