


REPLACING SIDE GLASS MD PREMIUM 60-100-120 AND/OR 24-40-48 WITH 3 OR 4/5 SHELVES.

It is recommended to have the service manual of the MD series (9123861 for the USA version or 9123792 for the Euro version) at hand.



1. **(Pass through only)** Remove the top and back panel(s) according prior procedures.
2. **(Solid back only)** Remove the top cover and the rear panel according prior procedures.
3. Open the drawer.
4. Remove the bolts that secure the brackets of the glass and remove the brackets.
5. Remove all broken glass and silicon residue and clean the surface.
6. Place the new glass and secure the glass to the machine with the 2 taptite bolts in each mounting bracket. To secure the glass with one or two clamps makes it easier.
7. Seal the edge between the bottom, black coloured, drip tray and the side glass with transparent Dow Corning 732 Silicon sealant (part.nr. 4302373). See white line in picture below.

Part numbers glass:

Side glass right, ass. MD 3 shelves 9220030S.

Side glass, left, ass. MD 3 shelves 9220031S.

Side glass right, ass. MD 4/5 shelves 9220032S.

Side glass, left, ass. MD 4/5 shelves 9220033S.

Note: Use a hammer and strong chisel in combination with a spatula to remove the glass. See next page.



